

**kerlite**  
5plus

PORCELLANATO  
CERAMICO  
SOTTILE

# FOREST\_KERLITE 5PLUS

Conforme | According to :  
ISO 13006-G (Gruppo/Group Bla)  
EN 14411-C (Gruppo/Group Bla)  
ANSI A137.3 (Unglazed gauged porcelain slabs)

NATURALE   

FORMATI  
SIZES



cm 100x300 sp. 5,5 mm



cm 33x300 sp. 5,5 mm



cm 20x180 sp. 5,5 mm



cm 20x120 sp. 5,5 mm

CARATTERISTICHE  
TECNICHE  
TECHNICAL  
CHARACTERISTICS

Resistenza allo scivolamento - Slip resistance

 DIN 51130 | DIN 51097 | BCRA/TORTUS | ANSI A326.3 | UNE 41901EX  
**R10** | **B (A+B)** | **μ > 0,40** | **DCOF ≥ 0,42** | **Clase 1**

Caricodi rottura (S) valore medio - Breaking strenght (S) average value

 ASTM C1505  
**≥ 175 lbf**

Resistenza alla flessione valore medio - Bending strenght average value

 ASTM C1505 | ISO10545-4  
**≥ 6.000 PSI** | **50 N/mm²**

Resistenza all'attacco chimico - Resistance to chemical etching

 ISO 10545-13 | ASTM C 650  
**LA-H-RESISTENTE/RESISTANT\*** | **Class A RESISTANT**

Resistenza alle macchie - Stain resistance

 ISO 10545-14 | ASTM C 1378  
**5 RESISTENTE/RESISTANT** | **Class A RESISTANT**

Resistenza all'abrasione profonda valore medio - Deep abrasion resistance average value

 ISO10545-6 | ASTM C1243  
**Conforme/Compliant**


Assorbimento d'acqua - Water absorption

 ISO10545-3  
**≤ 0,1%\***

Resistenza al gelo - Frost resistance

 ISO 10545-12  
**Resistente/Resistant**

Stonalizzazione - Deshading

 ANSI A137.1  
**V3** Noce, Acero - **V4** Rovere

\* No acido fluoridrico e derivati / Not resistant to hydrofluoric acid and derivatives

\*\*Valore riferito al materiale ceramico / Value refers to ceramic material

INFORMAZIONI  
SULLA PULIZIA  
INFORMATION  
ABOUT CLEANING



Visibilità delle impronte

METODO COTTOD'ESTE  
Questa classificazione specifica il grado di visibilità delle impronte rilasciate sul pavimento dopo il passaggio con scarpe sporche di polvere.  
**A** - Impronta non visibile  
**B** - Impronta poco visibile  
**C** - Impronta molto visibile.  
Consigliato solo in ambienti residenziali.

Tread mark visibility

COTTOD'ESTE METHOD  
This classification specifies the visibility degree of the tread marks left on the floor after walking with shoes dirty of dust.  
**A** - Tread mark not visible  
**B** - Tread mark not very visible.  
**C** - Tread mark very visible.  
Recommended for residential environments only.

**A** Noce

**B** Acero, Rovere



Facilità di pulizia

METODO COTTOD'ESTE  
Il metodo consiste nel classificare il grado di facilità nella rimozione dello sporco generico mediante pulizia manuale con detergente debole.  
**Grado 1** - Molto facile, nessuna resistenza dello sporco, rimozione immediata.  
**Grado 2** - Facile, leggera resistenza dello sporco, rimozione veloce.  
**Grado 3** - Meno facile, maggiore resistenza dello sporco, rimozione lenta. Si consiglia detergente forte. Consigliato solo in ambienti residenziali.

Cleaning easiness

COTTOD'ESTE METHOD  
The method consists in classifying the easiness grade in removing general dirt by manual cleaning with mild detergent.  
**Grade 1** - Very easy, no resistance of the dirt, immediate removal.  
**Grade 2** - Easy, light resistance of the dirt, fast removal.  
**Grade 3** - Less easy, higher resistance of the dirt, slow removal. A strong detergent is recommended. Recommended for residential environments only.

**1** Noce

**2** Acero, Rovere



Garantito 20 anni / Guaranteed 20 years

Residenziale e pubblico  
Residential and public

GARANZIA  
COTTOD'ESTE  
COTTOD'ESTE  
GUARANTEE

PROTEZIONE  
ANTIBATTERICA  
ANTIMICROBIAL  
PROTECTION

**P R ( ) T E C T**<sup>®</sup>  
ANTIBATTERICO - ANTIMICROBIAL